

## IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in this application.

5    --1. – 3. (Canceled)

4. (Currently Amended) A computer switching system comprising:

a user interface device for multiplexing signals output from a connected keyboard and  
cursor control device and for providing an interface to a video display;

10    a switch unit for enabling communication between said user interface device and a  
plurality of remotely located computers, said switch unit coupled to said user  
interface device by a single first connection; and

a plurality of computer interface modules each coupled to said switch unit by a single  
second connection, each of said computer interface modules coupled to at least  
15    one of said remotely located computers;

wherein video signals output from said remotely located computers are transmitted to said  
video display via said switch unit;

wherein said user interface device comprises an amplification circuit for automatically  
amplifying said transmitted video signals based on at least a synchronization signal transmitted  
20    with a component of said video signal;

wherein said user interface device receives ~~transmits signals from~~ said keyboard and said  
cursor control device signals, packetizes at least one of said keyboard or cursor control signals

and transmits said packetized signal with command data to said switch unit; and

wherein said switch unit interprets said ~~keyboard and cursor control device command~~  
data which identifies at least one of said remotely located computers, ~~signals~~ generates an

emulated keyboard ~~and~~ or cursor control device ~~signals~~ signal based on said packetized signal

5 and transmits said emulated ~~keyboard and cursor control device signals~~ signal to ~~a select one of~~  
said identified remotely located ~~computers~~ computer.

5. **(Currently Amended)** A system according to claim 4, wherein at least one of said first and  
second connections ~~each~~ comprise a series of twisted pair conducting wires.

10

6. **(Currently Amended)** A system according to claim 5, wherein each said component of said  
video signals is transmitted on one of said twisted pair conducting wires ~~of said first and second~~  
~~connections~~, and wherein said keyboard and cursor control device signals are transmitted on a  
separate one of said twisted pair conducting wires.

15

7. **(Currently Amended)** A system according to claim ~~[[6]]~~ 5, wherein ~~[[a]]~~ said  
synchronization signal is transmitted with ~~on~~ one of said components of said video signals on  
one of said twisted pair conducting wires.

20 8. **(Currently Amended)** A system according to claim ~~[[7]]~~ 4, wherein said synchronization  
signal is decoded by said user interface device.

9. **(Currently Amended)** A system according to claim 5, wherein said command data is transmitted with said keyboard and cursor control signals on a separate one of said twisted pair conducting wires.

5

10. **(Canceled)**

11. **(Previously Presented)** A system according to claim 4, wherein each of said plurality of computer interface modules receives power from one of said remote computers.

10

12. **(Currently Amended)** A system according to claim 4, wherein said ~~user interface device~~ comprises circuitry amplification circuit for said ~~amplifying~~ amplifies the amplitude and frequency components of said video signals by analyzing said synchronization signal.

15 13. – 15. **(Canceled)**

16. **(Currently Amended)** A system according to claim ~~[[13]]~~ 4, wherein said synchronization signal is a horizontal or vertical synchronization signal.

20

17. (Currently Amended) A computer switching system comprising:

a user station including a keyboard, cursor control device and video display;

a switch for enabling communication between said user station and a plurality of remotely

located computers, wherein said switch is coupled to said user station by a first

connection; and

a plurality of computer interface modules each coupled to a communication circuit of one

of said plurality of remote computers and each of said computer interface modules

coupled to said switch by a second connection;

wherein said user station receives keyboard and cursor control device signals, packetizes

at least one of said keyboard or cursor control device signals, and transmits said packet provides

~~keyboard and cursor control device signals~~ with command data to said switch;

wherein said switch interprets said command data in said packet to determine a

destination of said packet, emulates keyboard ~~and~~ or cursor control device signals, and transmits

said emulated keyboard ~~and~~ or cursor control device ~~signals~~ signal to ~~one of said remote~~

~~computers~~ destination;

wherein one of said computer interface modules receives video signals having red, green,

and blue components from one of said remote computers and encodes synchronization signals

onto at least one of said components for transmission to said user station through said switch;

and

wherein said user station analyzes said encoded synchronization signals to automatically

amplify one or more frequency components of said video signals.

18. **(Previously Presented)** A system according to claim 17, wherein each of said computer interface modules receives power from one of said remotely located computers.

19. **(Currently Amended)** A system according to claim 17, wherein at least one of said first and  
5 second connections ~~each~~ comprise a series of twisted pair conducting wires.

20. **(Currently Amended)** A system according to claim 19, wherein each said component of  
said video signals is transmitted on one of said twisted pair conducting wires ~~of said first and  
second connections~~, and wherein said keyboard and cursor control device signals are transmitted  
10 on a separate one of said twisting pair conducting wires.

21. **(Previously Presented)** A system according to claim 17, wherein said synchronization  
signals are encoded as negative signals.

15 22. **(Previously Presented)** A system according to claim 17, wherein said synchronization  
signals comprise horizontal or vertical synchronization signals.

23. **(Previously Presented)** A system according to claim 17, wherein said user station  
compares said synchronization signals to a signal of known shape to determine a degradation of  
20 said synchronization signals.

24. **(Previously Presented)** A system according to claim 23, wherein said user station amplifies said one or more frequency components of said video signals to compensate for said degradation.

25. **(Currently Amended)** A method for remotely operating a remote computer, said method

5 comprising the steps of:

receiving keyboard signals from a local keyboard at a user station;

receiving cursor control device signals from a local cursor control device at said user station;

transmitting said keyboard and cursor control device signals with command data to a  
10 central switch;

interpreting said command data and said keyboard and cursor control device signals, said central switch including a circuit for producing emulated keyboard and cursor control device signals at said central switch;

transmitting said emulated keyboard and cursor control device signals to said remote  
15 computer;

receiving video signals at said central switch from said remote computer in response to said emulated keyboard and cursor control device signals;

transmitting said video signals to said user station; and

amplifying at least one frequency component of said video signals based on

20 synchronization signals transmitted with said video signals to produce tuned video signals for display at said user station.

26. **(Currently Amended)** A method according to claim 25, said method further comprising the step of:

encoding said synchronization signals onto said video signals from said remote computer.

5 27. **(Currently Amended)** A method according to claim [[26]] 25, further comprising the step of:

analyzing said synchronization signals to determine a level of amplification for said at

least one frequency component of said video signals.

10 28. **(Currently Amended)** A method according to claim [[26]] 25, wherein said synchronization signals comprise horizontal or vertical synchronization signals.--